

TUBEMASTER 514 E



PROGRAMMABLE POWER SOURCE FOR ORBITAL WELD HEADS

The model 514 brings the benefits of true digital technology to the orbital welding customer: unparalleled accuracy, repeatability and reliability. Digital technology forever eliminates the need for periodic weld head calibration - rotation speed remains accurate regardless of head wear, and heads can be interchanged without time-consuming calibration. An intuitive touchscreen interface simplifies programming and control functions with easy-to-follow screens. Auto Program mode is only three screens deep, requiring the programmer to enter head model, tube O.D., wall and material.

- Unique auto programming
- Rugged design
- Operates fusion and wire feed heads
- Tough, black powder coat finish

TUBEMASTER 514 E

FEATURES

- 200 amp output
- Up to 100 levels per program
- Stores 100 weld programs internally
- Wire feed capability for wire feed Heads
- Auto Program automatically generates procedures
- Programmable "override limits" provide supervisory control
- Transfer programs and data to PCs or other power supplies using USB flash drive
- AutoTack automatically generates tack weld programs
- Large color LCD touch screen display
- Head mounted membrane switches eliminate remote pendant (certain models only)
- Help files provide immediate information/assistance
- Password protection of key functions
- Built-in printer allows program/QC report printout
- Detachable coolant recirculator with integral flow switch protection
- Emergency E-Stop
- Made in the USA



SPECIFICATIONS

Application	For use with many weld head models (GTAW process)
Functions controlled	Welding current output/current pulsing, weld head rotation, weld head wire feed speed
Output power	0 - 200 amps
Input power requirements (rated load)	115/230 VAC, 1 Ø, 4.0 KVA, 50/60 Hz
Internal memory capacity	100 weld programs
Unit of measurement	Inch and metric (selectable)
Program transfer	USB flash drive
Language (selection)	English, Spanish, German, French, others
Settable override limits	Individually scalable overrides on each function 0- 100%
Maximum open circuit voltage	80 V
Water and gas flow switches	Standard. Prevents damage to equipment and workpiece
Data recording/printout	Operator ID, weld ID number, program number, material, OD, wall thickness, date, time, weld head model, project, drawing, programmed parameters, etc.
QC parameter monitoring/recording/printout	Monitors and records any actual deviations from preprogrammed limits
Arc start type	HF
Operating/storage temperature	Operating: 0 - 120°F (-18 to 50°C) Storage: -20 to 140°F (-25 to 60°C)
Humidity	To 98% RH (non-condensing)



Morgan Industrial Technology
1702 West Boat St., Ozark, MO 65721
(417) 485-4575
sales@morganitech.com
www.morganitech.com