

T HEAD 419

ORBITAL WELD HEAD FOR MULTI-PASS GTAW PIPE WELDING


The Magnatech T model weld head is designed to make pipe-to-pipe and pipe-to-fitting welds. It is “full function” – with the capability of reproducing all the motions of a skilled manual welder. The T Head is used for larger diameter/heavy wall applications, requiring the precise weld process control of gas tungsten arc welding. Interchangeable guide rings provide mounting on the pipe, and allow the T Head to cover a broad size range. The T model weld head improves productivity by increasing duty cycle, reducing repair rates, and producing welds of consistent quality.

- Generates high quality welds
- Single or dual wire feeder option
- Rugged design
- State of the art technology

T HEAD 419

TORCH OSCILLATION (WEAVE)

Width, speed, and endpoint "dwell" independently programmable. Torch "cross seam" steering electronically controlled using remote pendant. Pulsed current automatically synchronized with torch oscillation.



3-AXIS POSITION ADJUSTMENT FOR FILLER WIRE NOZZLE

Multiple adjustments provide precise positioning of filler wire entry into weld puddle.

FILLER WIRE SPOOL

Use standard 1 kg (2 lbs) spools.

HEAD-MOUNTED WIRE FEEDER

Accommodates range of wire diameters.

WATER-COOLED TORCH

WELD HEAD MOUNTING/ROTATION

Guide rings attach head to pipe.

SPECIFICATIONS

*Guide rings come with a one year warranty

Application	Multi-pass orbital GTAW pipe-to-pipe, pipe-to-fitting
Cable length	7.6 m (25') standard. Extension cables available
Pipe (tube) size range	168 - 1524 mm (6 - 60") and larger
Filler wire module	Wire size: 0.8, 0.9, 1.0, 1.2 mm (.030", .035", .040", .045")
	Max. speed capability: 2540 mm/min. (100 IPM)
	Spool size: 1 kg (2 lbs) standard. 5 kg (10 lb) spool size optional
Oscillation module	Max. oscillation stroke amplitude: 16 mm (0.6725")
	Max. oscillation speed: 1520 mm/min. (60 IPM)
	Oscillation dwell: 0 - 1 second
	Cross seam adjustment: ± 6.4 mm (0.25") fine adjustment ± 38 mm (1.5") course adjustment
Arc gap control module stroke	66 mm (2.6") stroke. Additional mechanical adjustment allows welding heavier wall pipe
Torch propulsion module	250 mm/min. (10 IPM) maximum rotation speed
Water-cooled torch	300 A continuous
Torch adjustment capability	Torch lead/lag adjustment: ± 15 degrees (manual)
	Torch tilt adjustment: ± 10 degrees (manual)
Power supply compatibility	Pipemaster 515, Pipemaster 516



Morgan Industrial Technology
 1702 West Boat St., Ozark, MO 65721
 (417) 485-4575
 sales@morganitech.com
 www.morganitech.com