

Now you can get Magnatech Quality in a Micro.

INTRODUCING THE MAGNATECH M500.

An ultra low profile orbital weld head designed for precision fusion welding of tube and fitting sizes from 1/8" - 1/2" OD (3.2mm-12.7mm).

Measuring only 10" long and equipped with the industry's narrowest configuration flush cartridge and collet, the M500 is ideal for restricted clearance micro-fit welding applications.

M805 Mini

M500 Micro





SALES & SUPPORT 417-485-4575

1702 WEST BOAT STREET OZARK, MO 65721

sales@morganitech.com www.morganitech.com

Magnatech Model 500

Micro Orbital Weld Head for Fusion Welding of Tube and Fitting

Advantages

• Housing body made of Torlon 5030 material rated for an unprecedented 525° F allows exceptional duty cycle without the need for water cooling.

• Collet frames hinge on the same side, allowing greater access to tight clearance welds.

- Durable stainless steel rotor insures long wear life.
- High dielectric Kapton[®] inserts on both sides of the cartridge resist arc-overs and are user-replaceable.
- Dual bearing support for internal gear drive.

Additional Features

• Available in three configurations to fit various power supplies.

- Accepts standard 9-500 tube clamp inserts.
- Quick release thumb screw assembly eliminates the need for tools when changing clamping cartridges.
- Collets are available for any tube and fitting size from 3.2mm to 12.7mm (0.125" 0.5").
- Standard 25 foot cable length.

Magnatech Model 805

Mini Orbital Weld Head for Fusion Welding of Tube and Fitting

Advantages

• Low profile, robust design is ideal for restricted clearance welding applications.

• Digital technology forever eliminates the need for periodic calibration. Rotation speed remains accurate regardless of wear.

• Encoder motor also detects and prevents jams to avoid accidental damage and costly repairs.

• Internal full exchange water cooling technology allows true 100% duty cycle performance.

Additional Features

• Double-clamping scissor action design with precise tube centering simplifies work piece fit-up and eliminates tack welding in many cases.

• Easy access collet clamp tension adjustment.

• Collets are available for any tube and fitting size from 3mm to 16mm (0.125" - 0.625").

