



# 516

## PROGRAMMABLE CONTROLLER FOR ORBITAL WELD HEADS

The latest generation of Pipemaster controllers are the result of a new direction in power source design. The Pipemaster 516 brings the benefits of digital technology to the orbital welding customer: unparalleled accuracy, repeatability, and reliability. Digital technology forever eliminates the need for periodic weld head calibration - motor speeds and response characteristics remain accurate and stable regardless of wear, and weld heads can be interchanged without time-consuming calibration.

- Unique auto-programming for multi-pass welding
- Easy to program
- Rugged design

# PIPEMASTER 516

## FEATURES

- Multi-pass welding of pipes/tubes/tubesheets
- Full function capability (torch rotation, filler wire feed, electronic arc gap control, electronic oscillation)
- Operates all models of Magnatech weld heads (GTAW process)
- Current programming and pulsing controlled by Pipemaster controller – not the power supply
- Amperage output determined by power source selection
- Autoranging power input eliminates all internal modifications
- Up to 100 levels per program (time-based programs)
- Stores 100 weld programs internally
- AutoProgram automatically generates procedures
- Programming and operation guided by simple prompts
- Teach mode allows rapid program development
- Programmable “override limits” provide supervisory control
- Weld parameter monitoring/out-of-limits reporting for QA/QC purposes
- Transfer programs and QC data to PC using USB flash drive/memory key
- AutoTack automatically generates tack weld programs
- Large color LCD pendant display
- Stainless steel case
- Help files provide immediate information/assistance
- Password protection of key functions
- Waterproof pendant with 7.6 m [25'] cable
- Auto rewind feature unwraps cable at weld completion
- All weld head functions capable of synchronization with pulsed current output
- Selectable position or time-based programming
- Integral switch prevents welding without torch gas flow
- Bluetooth printer option



## SPECIFICATIONS

Application	For use with many Magnatech weld head models (GTAW process), welding lathes, and dedicated weld systems
Functions controlled	Weld current output/current pulsing, weld head rotation, weld head wire feed speed, electronic arc voltage control, electronic torch oscillation, electronic torch cross-seam adjustment
Output power	Power source dependent
Input power requirements (rated load)	110 – 230 VAC, 1 Ø, 4.0 KVA, 50/60 Hz autoranging (no modifications necessary)
Protection level	Controller IP-23; pendant IP-65
Internal memory capacity	100 weld programs
Units of measurement	Metric and inch (selectable)
Program transfer	Solid state digital media (disk-on-key, memory key)
Language selection	English, Spanish, German, French, others
Settable override limits	Individually scalable overrides on each function 0 – 100%
Water and gas flow switches	Standard. Prevent damage to equipment and workpiece
Data recording/printout	Operator ID, weld ID number, program number, material, OD, wall thickness, date, time, weld head model, project, drawing, programmed parameters
Printer (optional)	Freestanding. Bluetooth. Integral rechargeable battery with charger. IP-54 rating
QC-parameter monitoring/recording/printout	Records actual parameters and deviations from preprogrammed limits
Arc start type	High voltage impulse
Operating/storage temperature	Operating: -18 to 50° C (0 to 120° F) Storage: -25 to 60° C (-20 to 140° F)
Humidity	To 98% RH (non-condensing)



**Morgan Industrial Technology**  
1702 West Boat St., Ozark, MO 65721  
(417) 485-4575  
sales@morganitech.com  
www.morganitech.com